



LED SOLAR STREET LIGHT

- . Ultra thin design, Small size, easy transportation.
- . Intelligent radal scan, when people come, the brightness. of the lamp is 100%. Afte the person leaves, the brightness of the lamp is 30%.reduce electricity consumption.
- . Removable rear cover, Easy maintenance and replacement of power supply. . Easy installation.can operate by ourselves.
- . Widely used in street, garden villas, country roads, factories,
- schools, squares.parks and other aeas in need of lighting.

30\//

40\\/


Product electronic parameters Power 10\// 201/1/

FOWEI	1000	2000	30 00	4000
LED Quantity	42	64	60	80
Beam angle	60°×150°	80°×150°	65°×135°	60°×130°
Chip n	nodel		3030	


Chip model	3030		
Chip brand	Philips/Osram/Cree		
Input voltage	DC12V		
Color temperature	3000-6500K		
CRI	≥70		
Protection level	IP65		
Operating temperature	0°C ~+40°C		
Lamp body material	Aluminum		
Mounting rod diameter	Ø60MM		
Warranty	2-3 years		
Luminaire efficacy	160 lm/w		

Battery product	specifi	cation	S		
Items		Stan	Remark		
Nominal voltage	12.8 V				
Typical capacity	9Ah	15Ah	18Ah	21Ah	At 0.2C discharge rate
Max continuous discharge current	4A	4A	6A	6A	
Over protection current	35±5A				100±30ms
Discharge cut-off voltage	10V				
Charge voltage	14.4±0.1V				CC-CV
Charge current	4A	4A	6A	6A	CC-CV
Inner resistance	≤100mΩ	≤80mΩ	≤75mΩ	≤65mΩ	
Operation	Charge			0°C∼+45°C	
temperature range	Discharge				-20°C∼+60°C
Storage temperature range	0°C∼40°C			Capacity 80%	
Humidity	5%≤RH≤85%				
Shell material	PVC				
Weight	About 1.2 ±0.05Kg	About 1.9 ±0.1Kg	About 2.25 ±0.05Kg	About 2.7 ±0.1Kg	
Size (L*W*H)	270*185*30mm				
Protection function	Over charge protection, Over discharge protection, Over current protection, Balanced function				

Product Size



10W



]								
)								
days, every night bright 10 hours, luminous area is large,								
Ç								

84*33*24cm

- Ultra thin design, Small size, easy transportation, cheap price.



Unit: mm

9.3kg

8kg


Product in stock

Long standby




PRODUCT

MASS PRODUCTION



Ultra-thin lamp body

PRODUCT AGING



PRODUCT LOCATION REAL SHOT